



- For best results, select medium to heavy weight fabrics when embroidering Fringe designs. Use the stabilizer appropriate for the fabric or the garment.
- Always sew a test sample before stitching on the actual garment.
- Use contrasting bobbin thread when sewing small fringes or multi-layer fringe. This
  will help ensure that you clip the correct threads when making the fringe.
- You will need small, very sharp scissors when clipping the front of the fringe.
- The Embroidery Wand, available at your local dealer, is a handy gadget that looks like
  a large needle without the eye. This allows you to pull the loops of the fringe through
  to the front quickly and easily, without distorting the stitches.
- Test the embroidery on scarp fabric using the same fabric, stabilizer, needle and thread you intend to use for the completed project.
- Hooping stabilizer and fabric together as one will yield the best results, just as it does for all embroidery.

## Stitch &Clip

- After all of the embroidery work is finished, remove the fabric from hoop.
- From the right side of the fabric, carefully clip threads as described below to achieve the desired fringe type.
- Use The Embroidery Wand, available at your local dealer; to safely lift and loosen the fringe ends from the front of the garment or project.
- Clip the threads with small sharp scissors.
- Remove any loose threads by gently rubbing the back.
- Steam fringe lightly for a few seconds, and then use your fingers to gently straighten and flatten the fringe. DO NOT PLACE THE IRON DIRECTLY ON THE FRINGE.



The fringe adds a special dimension that makes the designs so cute!





