

Trousers "Julia"

Model 120-26

Sizes 36-48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter) (do not click on "Adjustment to page size"!)
2. Check the square – if it is 10x 10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size (the overview of the cut parts is on the pattern sheet). **Important:** Instructions do not include seam allowances, unless otherwise indicated.

SUPPLIES

- 1.1 – 1.5 m rayon jersey "Marzio", 150 cm wide
- 0.3 – 0.4 m rayon jersey, plain, 140 cm wide
- 0.7 – 1.0 m sewing track elastic, 4 cm wide
- 1.1 – 1.4 m flat cord, 1.5 cm wide
- Remnant of iron-on stabiliser
- Remnant of edge tape (Vlieseline)

Optional accessories

- BERNINA overlocker
- Dual Feed

CUTTING

- 1 2 × front part
- 2 2 × hip yoke
- 3 2 × pocket bag
- 4 2 × back part
- 5 4 × cuffs

Waistband 90/93/96/99/102/105/110 cm × 10 cm, final width 5 cm.

INSTRUCTIONS

1. Iron the edge tape on the wrong fabric side of the pocket mouths. Sew the pocket bags right side on right side on the front parts, clip the seam allowances, turn it over and topstitch the edge of the pocket mouth at the width of the foot. Pin the hip yoke beneath the front part according to the marking. Close the pocket bag. Fix the pocket bag on the upper edge and the side seam. Close the side, the bottom, the crotch and the inner leg seams.
2. Iron a piece of stabiliser on the front centre of the wrong fabric side of the outer waistband. Starting from the front centre, sew a vertical buttonhole for the flat cord, each 1.5 cm to the left and to the right. Place the waistband right side on right side and close it to a ring, leaving an opening for the elastic in the inner part. Iron the waistband on the fold, wrong fabric sides inwards. Divide the lower edge into quarters. Sew the waistband right side on right side along the upper edge of the trousers, gathering the fabric.
3. Insert the elastic into the waistband and close it to a ring. Topstitch the waistband between two sewing tracks of the elastic, stretching the elastic in doing so. Pull the cord through the buttonholes and tie the ends.
4. Sew the cuffs right side on right side together with the lower edge. Close the inner leg seams and turn the cuffs. Pin the open edges on top of each other. Pin the cuffs right side on right side on the legs and while sewing them, gather the extra width of the trouser legs.



made to create **BERNINA**