

Men's shirt "Yannik"

Model 222-50

Size 48 – 58, length
center back approx. 76 cm



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

Important: Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 1.6–1.9 m cotton fabric, 140 cm wide
- Woven interlining G 785 (Vlieseline)
- 5 buttons, 15 mm (Union Knopf)

OPTIONAL BERNINA ACCESSORIES

- [Button Sew-On Foot #18](#)

CUTTING

- 1 2× front part
- 1 2× facing
- 2 2× yoke on the fold
- 3 1× back part on the fold
- 4 2× collar on the fold
- 5 2× sleeve with cut hem facing

INSTRUCTIONS

1. Iron the woven interlining on one collar part and the facing. Pin the facing right side on right side along the front edge and sew it on starting from the small horizontal line at the neckline. Cut back the allowances in the corner and clip the allowance at the horizontal line close to the seam line. Turn the facing to the inside and fix it with pins at the neckline and the shoulder.
2. Close the pleat on the back part with pins. Pin the first yoke right side on right side on the back part and the second yoke right side on wrong side on the back part. Close the seam. Sew the front parts right side on right side on the outer yoke. Iron the allowances towards the yoke. Fix the inner front edges of the yoke with folded-in allowances with pins. Topstitch the yoke seams on the front and back parts from the right, also stitching the inner yoke.
3. Sew the collar right side on right together along the narrow edges and outer edge. Cut back the allowances in the corners, turn the collar inside out and iron it. Sew the outer collar right side on wrong side along the neckline. Clip the allowances on the back part. Place complete collar lengthwise as it will be in the finished garment. Pin the outer and the inner collar on top of each other below the fold. Fold in the allowance of the open long edge of the inner collar, fix it with pins and sew it on.
4. How to sew the fake cuff: Remove the allowance of the lower edge on the cut hem facing and iron it to the wrong side. Fold it a second time inwards and iron the new folded edge too. Topstitch the layers along the marking "Stitching line". Iron the sleeve upwards.
5. Sew in the sleeves. Close the sleeve seams and the side seams in one go. Place the allowances on the sleeve cuff after finishing to the back and topstitch them.



made to create **BERNINA**

INSTRUCTIONS

6. Sew the lower edge of the facing right side on right side on the lower edge of the shirt and turn it inside out. Hem the shirt. Topstitch the edges of the front parts and the collar. Sew the topmost buttonhole where it is illustrated and spread the following ones evenly at a distance of 10–11 cm. Sew on all buttons with the Button Sew-On Foot.



made to create **BERNINA**