

Jeans "Tilda"

Model 124-13

Size 36–48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

Important: Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 1.5–2.1 m stretch denim, 140 cm wide
- 1 zip, 14–18 cm
- 1 jeans button, 18 mm
- Woven interlining G 700 (Vlieseline)
- Seam tape
- Woollen embroidery thread
- Wool yarn needle
- Firm stabiliser
- BERNINA Dual Feed or [Walking Foot #50](#)
- [Free embroidery file](#)

CUTTING

- 1 2× front part
- 2 2× hip yoke
- 3 2× pocket bag
- 4 2× rear yoke
- 5 2× back part
- 6 2× hip pocket
- 7 2× waistband on the fold

Slit facing: 15 up to 20×7 cm, final width 3.5 cm. Belt loops: approx. 50×3 cm, final width 1 cm.

INSTRUCTIONS

1. Iron Vlieseline on one side of the waistband. On the front part, iron the seam tape on the pocket mouth and let everything cool off thoroughly.
2. Mark the placement line of the upper edge of the pocket on the back parts. Sew the rear yokes to the back parts. Fold the allowances apart, finish and topstitch them. We recommend a stitch length of approx. 3.6 when topstitching the seams.
3. Hoop firm stabiliser in the embroidery hoop. Embroider colour 1 (placement line of the upper pocket edge). Place the left back part on top and baste it in place. Embroider a row of flowers with the woollen yarn, using the wool yarn needle to do this and increasing the thread tension if necessary.
4. Embroider the other embroidery file on the left hip yoke as described above. The placement line for size 36 has been digitised, other sizes are placed centrally to this line.

5. Sew the front pocket bags right side on right side along the pocket mouth. Iron the allowances inside the pocket bag. Turn the pocket bag inwards and topstitch it. Pin the hip yoke with the marking below the pocket mouth. Close the pocket bag.
6. Close the front centre seam beneath the slit marking.
How to sew in the zip: On the front part, iron the fly facing on the right side along the fold and on the left side approx. 5 mm further towards the edge. Sew the zip under the underlap. Pin the front centre of the right front part to the front centre of the left front part. Sew the loose zip tape on the facing. Topstitch the overlap. Fold the fly facing lengthwise, right side folded in and sew the lower edge together. Turn the facing inside out and finish the long edge. Pin the fly facing right sides together under the underlay and sew it onto the seam of the zip. Pin the lower edge and sew it on the zip tape. Sew two bartacks in the topstitching seam of the overlap: one in the curve, the second below the end of the slit.
7. Add decorative stitching to the back pockets if desired. Hem the top edge and iron the side allowances to the wrong side. Sew the pockets on the back parts.
8. Close the side seams, finish the allowances and fold them to the back. Narrow-topstitch the seams once and then again at a distance of 6 mm. Close the rear centre seam and topstitch them like the side seams. Close the inner leg seams.
9. Finish one long edge of the strip for the belt loops. Fold in the second long edge and place the finished one on top. Topstitch the long edges. Cut 5 pieces of 9 cm each. Pin the loops to the front part, approx. 4 cm behind the side seams and to the rear centre. Sew the upper edge of the waistband right side on right side together. Clip the allowances in the curves. Place the waistband wrong side on wrong side and iron the upper edge. Sew the outer side of the waistband right side on right side along the upper edge of the trousers. Close the narrow edges of the waistband and cut off the excess length at the overlap. Fold in the allowance of the inside waistband edge. Topstitch the waistband all around from the right. Sew the buttonhole and press in the button.
10. Cut off the allowance on the trouser's legs. Sew the hem 1 cm above the edge with a triple straight stitch and fray the lower edges.

