

Bag "Olivia"

Model 121-11

Height 32 cm



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

Important: Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 0.7 m metallic synthetic leather, 140 cm wide
- Remnant of fabric lining
- "Extra-Strong" sewing thread

OPTIONAL BERNINA ACCESSORIES

- Dual Feed or [Walking Foot #50](#)

CUTTING

- 1 2× bag on the fold
- 1 2× facing on the fold (top edge up to the dotted line)
- 2 1× bottom on the fold, including the facing

Cut the following without allowances: Handle 45×9 cm, final width 4.5 cm, if required even longer. Tie strap 120×2.5 cm, final width 1.2 cm. Cord stopper 8×2 cm. Lining of parts 1 and 2 from lower edge up to facing line.

INSTRUCTIONS

1. Sew the facing right side on right side along the upper edge of the bag. Place the allowances towards the facing and topstitch them.
2. Sew the bottom and the bottom facings right side on right side between the bag parts and facings, leaving a gap for the tie strap at the slit markings. Separate the allowances of all facings and the bag above the slits including the gap area. Clip the allowances of the bag beneath the slits vertically up to the seam and from there, place all allowances in the bottom and topstitch them continuously.
3. Sew inside pockets on the lining as desired. Sew the lining bottom between the lining bag parts, leaving an opening to turn it over on one side. Finish the edge of the facing with the lining. Turn the bag over. Pin the gaps of facing and bag on top of each other. Topstitch the slit on the bag. Mark the buttonholes on the bag. Fix the facing in the buttonhole area. Sew one sewn buttonhole each using stitch length 3.6, 20 mm long and 5 mm wide. Cut open the buttonholes.
4. Sew the handle and the tie strap. Pin the handle to the upper edge of the bottom and stitch it on as shown. Insert the tie strap.
5. Topstitch the longitudinal edges of the cord stopper. Close it to a ring with 1 cm allowance. Turn the ring over, separate the allowances, thread the ends of the strap and topstitch the stopper vertically in the middle. Do not sew over the strap. Knot the cord ends.

