

Sweatshirt "Luna"

Model 121-30

Size 36-48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

Important: Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 0.5–0.6 m sweatshirt fabric, in white, 155 cm wide
- 0.7–0.8 m sweatshirt fabric, in black, 155 cm wide
- 0.2 m cuff fabric, 100 cm wide
- 0.2 m space fabric, 145 cm
- 1.2–1.5 m flat cord, 8 mm wide

OPTIONAL ACCESSORIES

- Elastic sewing thread "SabaFLEX" (Mettler)
- Overlocker
- [Walking Foot #50](#)
- [Eyelet Embroidery Attachment](#)

CUTTING

Fabrics must be washed beforehand! Preparing the paper cut: Cut the patterns for front and back parts as well as for the sleeves apart along the dividing line. Cut the hems on the front and the back parts with at least 2.5 cm allowance each.

- 1 1 × upper front part on the fold (in white)
- 1 1 × lower front part on the fold (in black)
- 2 1 × upper back part on the fold (in white)
- 2 1 × lower back part on the fold (in black)
- 3 2 × upper sleeve (in black)
- 3 2 × lower sleeve (in white)

2 sleeve cuffs sizes 36–38: 19×12 cm, final width 6 cm.

For sizes 40/42 20 cm, 44/46 21 cm and 48 22 cm.

Collar cuffs 45/46/46/47/47/48/48×4 cm, final width 2 cm.

Space fabric (Attention: do not iron!): Pocket 10.5×10.5 up to 12×12 cm. Sleeve strips 38 up to 45×10.5 cm.

INSTRUCTIONS

1. Hem the upper edge of the pocket. Pin the sleeve strip according to the markings (joining line) right side on right side on the upper sleeve and sew it on. Fold the strip down and pin it in place. Thread the Overlocker with a 4-thread overlock or a 3-thread super-stretch, using the "SabaFLEX". Sew all upper parts right side on right side on the lower parts. Sew the pocket with folded-back allowances on the left side of the front part according to the marking.



INSTRUCTIONS

2. Close the shoulder seams. Close all cuffs to a ring. Divide the neckline and the collar cuffs into quarters. Pin quarter by quarter together and sew the stretched neckline cuff along the neckline. Place the allowances inside the front and the back parts and narrow-topstitch them from the right. **Tip:** Use the elastic sewing thread for this, so that the thread does not break when tightened. Alternatively, use a narrow zigzag stitch.
3. Sew in the sleeves right side on right side. Close the sleeve and side seams in one go, if necessary, baste them with the sewing machine first. Pin the sleeve cuff and the sleeve hem quarter by quarter on top of each other and sew it on.
4. Reinforce the wrong fabric side of the front part with a remnant of Vlieseline at half hem height (see marking) on the right and the left of the front centre. Insert 2 eyelets with the Eyelet Embroidery Attachment. Alternatively, use two metal eyelets. The sweater is best hemmed with the coverstitch (Overlocker or Cover/chainstitch machine). Insert the cord and knot the ends.



made to create **BERNINA**