

# Coat "Julia"

## Model 121-34

### Size 104-134



#### PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!) )
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

**Important:** Instructions do not include seam allowances, unless otherwise indicated!

#### SUPPLIES

- 0.7–1 m coated cotton fabric, 150 cm wide
- Remnant of coated cotton fabric, 140 cm wide
- Open-end zip, 35–40 cm
- 4 presser buttons, 12 mm
- 0.7–0.8 m anorak cord
- 2 cord stoppers
- 2 eyelets, 5 mm
- 35–40 cm elastic, 2 cm wide

#### OPTIONAL BERNINA ACCESSORIES

- [Zigzag Foot with Non-Stick Sole #52](#)

#### CUTTING

For the smaller sizes we recommend a softer fabric than the original.

- 1 2× front part
- 1 1× zip facing on the fold
- 1 1× back part on the fold
- 1 1× collar (2 sides on the fold)
- 1 4× hood
- 1 2× sleeve

2× front part pocket for sizes 104/110: B 10×H 10 cm, for sizes 128/134: B 12×H 14 cm.

2× front part flap: pocket width plus 0.5 cm×H 7 cm, final width 3.5 cm.

1× back part pocket for sizes 104/110: approx. B 14×H 11 cm, for sizes 128/134: approx. B 15×H 15 cm.

2× back part flap: pocket width plus 0.5 cm×H 7 cm, final width 3.5 cm.

Piping 60 to 70×3.5 cm, visible width 5 mm.

#### INSTRUCTIONS

1. Fold the piping lengthwise with the wrong side inwards. Sew the piping on the front side seams of the jacket. Place the back part right side on right side on top of it and close the side seam. Fold the allowances to the front and topstitch them. Close the shoulder seam.
2. Close all darts on the hood parts. Close the centre seams. Place the allowances apart towards two opposite sides and topstitch them. Insert the eyelets at the markings on the outer hook. Sew the front edges of the hood. Narrow-topstitch the front edge and the rest at a distance of about 2 cm. Insert the cord through the



## INSTRUCTIONS

eyelet. Attach the cord stopper. **Tip:** If the cord does not fit through the stoppers easily, simply wrap the ends with adhesive tape.

3. Pin the hood to the neckline according to the markings and on top of it place one long side of the collar and sew both on. Sew the zipper facing on the upper curve and the lower edge and turn it over. Separate the zip and pin both parts right side on right side on the front parts. Place the zip facing on top of the zip half on the left front part and fix it with pins. Fold the curve of the zip facing outwards along the fold line and use it to "wrap" the top end of the zip. Sew in the zip.
4. Pin the loose collar edge with the allowance folded over. Topstitch the collar and the front edge. Hem the jacket.
5. Sew all pocket flaps along the sides and turn them over. Hem the upper edges of the pockets. Sew the pockets on the front parts and the back part, place and sew the flaps at a distance of 1.5 cm above.
6. Close the sleeve seam up to 2 mm after the folded edge on the hem. Hem the sleeves and narrow-topstitch the lower edge. **Tip:** As small children's sleeves are difficult to hem, they are usually hemmed before the sleeve seam is closed. But with the elastic, this becomes difficult. Therefore turn the sleeve inside out and sew the hem on the right side of the fabric. First hem, then close the sleeve seam. Alternatively, simply omit the elasticity.
7. Insert the elastic and sew together to a comfortable width, approx. 14 up to 17 cm each. Slightly gather the top shaping and sew in the sleeve.



made to create **BERNINA**