

# Skirt "Sarah"

## Model 320-15

### Size 36-48



#### PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!) )
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size.  
(The overview of the cut parts is on the pattern sheet.)  
**Important:** Instructions do not include seam allowances, unless otherwise indicated!

#### SUPPLIES

- 1.7 m checked fabric, 145 cm wide
- Seam concealing zip, 22 cm
- Fabric lining G 700

#### OPTIONAL BERNINA ACCESSORIES

- Dual Feed or [Walking Foot #50](#)
- [Invisible Zipper Foot #35](#)

#### CUTTING

- 1 1× front part on the fold
- 2 2× front waistband on the fold
- 3 1× back part on the fold
- 4 2× back waistband on the fold

If necessary belt loop approx. 28×3 cm, final width 1 cm.

#### INSTRUCTIONS

1. Iron the fabric lining on one waistband part each and let them cool off thoroughly. Place all pleat folds which are visible from the right side according to the arrows right side on right side on top of each other and topstitch them up to the horizontal line. Align the pleats so that the 6 cm long markings lie exactly behind the seam. Iron in the pleats. Depending on the fabric, narrow-topstitch the lower folds (invisible from the outside) up to twice the hem width.
2. Sew in the zip with foot #35. Close the side seams. Close the right side seams of the waistband parts. Sew the upper edges of the waistband and turn them over. Sew the belt loops, divide them into 4 pieces and pin them to the upper edge of the skirt. Sew on the waistband right side on right side with the underlap on the back part extending the zip. Sew the narrow edges of the waistband and turn them over. Topstitch the loose edge of the inner waistband in the seam shadow from the right. Sew on the belt loops beneath the waistband, fold them up and sew them on the upper edge of the waistband.
3. Hem the skirt with the blindstitch foot. Press the hem and the pleats in the hem area. Narrow-topstitch the lower pleat folds from the inside completely.

