

Sweatshirt "Cosy"

Model 321-16

Size 36-48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

Important: Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 1.8–1.9 m sweatshirt fabric, 150 cm wide
- Seam tape

OPTIONAL ACCESSORIES

- Elastic sewing thread "SERAFLEX" (Mettler)
- BERNINA Overlocker L 890
- BERNINA Embroidery machine
- Free embroidery file

CUTTING

- 1 1× centre front part on the fold
- 2 2× side front part
- 3 1× centre back part on the fold
- 4 2× side back part

Collar: Depending on the elasticity of the fabric, cut in or at 90° to the grain, using the stretchier option. Nevertheless, cut at least 2 cm allowances along the narrow edge. Before sewing on the collar, check whether the head fits through, otherwise widen it slightly. Collar for sizes 36/38: 49 cm, for sizes 40/42: 50 cm, for sizes 44/46: 51 cm long, height 9 cm, final height 4.5 cm.

INSTRUCTIONS

1. Embroider the logo "Hummingbird" approx. 0.5 cm beneath the seam line on the rear centre. Alternatively, sew the bird in free-motion embroidery according to the pattern piece or create a small appliqué.
2. Iron seam tape on the seam allowances on the back parts in the area from the shoulder to the marking (side back parts).
3. Set the overlocker for a 3-thread superstretch. **Tip:** "SeraFLEX" also ensures permanently secure seams. Close the shoulder seams of the centre parts.
4. Temporarily close the collar with a straight stitch to form a ring and fold it lengthwise. Try on the collar: if the head fits through, everything is fine, but this turns out differently depending on the elasticity of the material. If



INSTRUCTIONS

collar is too tight, let seam allowance out accordingly. Shorten the remaining length allowance if necessary. Pin the open edges together and divide the edge into quarters. Also quarter the length of the neckline by placing the centre front on the centre back and then divide the length in half again. Sew the stretched collar along the neckline, pinning the collar seam to the centre back. **Tip:** Depending on the material, first shape the collar on the ironing board, pin it down and stretch the open edges under steam to match the length of the neckline edge.

5. Close the upper seams of the sleeves. Sew the side front and back parts right side on right side on the centre parts.
6. Hem the sleeves with the coverstitch machine, if desired. Close the lower seams of the sleeves and the side seams continuously. Iron up the hem and sew it on with the coverstitch. **Tip:** As an alternative, sew with a 4–6 mm wide twin needle and a narrow zigzag stitch.



made to create **BERNINA**