

Panel skirt "Diamond"

Model 323-13

Size 36-48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
 2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
 3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
 4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)
- Important:** Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 2.0 m lyocell, 230 g/lm, 145 cm wide
- 0.6–0.7 m lining, 145 cm wide
- Woven interlining G 700
- 1 seam zip, 22 cm
- [Invisible Zipper Foot #35](#)
- Seam tape

CUTTING THE OUTER FABRIC

- 1 1 × centre front part on the fold
- 2 2 × side front part
- 3 1 × front facing on the fold
- 4 1 × centre back part on the fold
- 5 2 × side back part
- 6 1 × rear facing on the fold

CUTTING THE LINING

- 7 1 × front part on the fold
- 8 1 × back part on the fold

INSTRUCTIONS

1. Iron the interlining on the facings. Iron seam tape under the left side seam in the area of the zip.
2. **Outer fabric:** Sew the side front parts right sides on right sides to the centre part, and accordingly also sew the back parts together. Place the front part on top of the back part, close the right side seam and the left side seam below the slit mark. Fit the Presser Foot #35 and sew the zip in place.
3. **Lining:** Sew the facings to the corresponding skirt piece. Close the later left side seam between the slit marks and the other above the lower slit mark. Stitch the facing to the top edge of the skirt, turning the edges of the facing inside out at the beginning and end wrong side on wrong side so that there is a gap of about 1 cm to the zip. Place the zip with allowance wrong side on wrong side on top of it. Sew the narrow edge of the facing and the allowance of the zip edge together on the zip. Completely sew on the facing, stitching crosswise above the zip. Fold the facing inwards and topstitch the upper edge. Hem the skirt.

